



Pneumatic Screwdrivers

Push Type

Lever Type

Elbow Type

Gun Type





Technical specification

Specification	Rotating speed (rpm)	Weight (G)	Length (mm)	Outer diameter (mm)	Air Pressure (Kg/cm ²)	Minimum Pipe Diameter (mm)	Air Consumption (m ³ min)	Torque Range (kgf.cm)	Precision (%)	Locking Ability	
										Mechanical tooth benchmark (T)	Self-tapping (2T)
RGP-Q10PB	1000	480	180	34	6.0	5.0	0.2	0.5-2	± 3	M1.0-M2.2	M1.1-M1.7
RGP-Q20PB	1000	480	180	34	6.0	5.0	0.2	1-8	± 3	M1.7-M3.3	M1.3-M2.7
RGP-Q30PB	1800	480	180	34	6.0	5.0	0.28	3-17	± 3	M2.2-M4.2	M1.7-M3.2
RGP-Q35PB	2200	480	180	34	6.0	5.0	0.28	3-20	± 3	M2.2-M4.5	M1.7-M3.5
RGP-Q38PB	1800	480	180	34	6.0	5.0	0.28	3-25	± 3	M2.2-M4.7	M1.7-M3.8
RGP-Q40PB	1000	480	180	34	6.0	5.0	0.28	5-30	± 3	M2.8-M5.0	M2.2-M4.0
RGP-Q45PB	800	480	180	34	6.0	6.35	0.3	8-40	± 3	M3.3-M5.7	M2.7-M4.4
RGP-Q48PB	1700	790	215	42	6.0	8.0	0.55	5-45	± 3	M2.8-M5.8	M2.2-M4.7
RGP-Q50PB	1400	790	215	42	6.0	8.0	0.55	7-50	± 3	M2.9-M6.0	M2.6-M4.9
RGP-Q55PB	1000	790	215	42	6.0	8.0	0.55	7-65	± 3	M2.9-M6.4	M2.6-M5.4
RGP-Q60PB	550	790	215	42	6.0	8.0	0.55	15-95	± 3	M4.1-M7.0	M3.1-M6.0
RGP-Q65PB	300	810	215	42	6.0	8.0	0.55	30-180	± 3	M5.1-M9.3	M4.0-M7.2
RGP-Q68PB	250	810	215	42	6.0	8.0	0.55	50-250	± 3	M6.0-M11.0	M4.9-M8.7

Lever Type



Technical specification

Specification	Rotating speed (rpm)	Weight (G)	Length (mm)	Outer diameter (mm)	Air Pressure (Kg/cm ²)	Minimum Pipe Diameter (mm)	Air Consumption (m ³ min)	Torque Range (kgf.cm)	Precision (%)	Locking Ability	
										Mechanical tooth benchmark (T)	Self-tapping (2T)
RGP-Q10LB	1000	480	180	34	6.0	5.0	0.2	0.5-2	± 3	M1.0-M2.2	M1.1-M1.7
RGP-Q20LB	1000	480	180	34	6.0	5.0	0.2	1-8	± 3	M1.7-M3.3	M1.3-M2.7
RGP-Q30LB	1800	480	180	34	6.0	5.0	0.28	3-17	± 3	M2.2-M4.2	M1.7-M3.2
RGP-Q35LB	2200	480	180	34	6.0	5.0	0.28	3-20	± 3	M2.2-M4.5	M1.7-M3.5
RGP-Q38LB	1800	480	180	34	6.0	5.0	0.28	3-25	± 3	M2.2-M4.7	M1.7-M3.8
RGP-Q40LB	1000	480	180	34	6.0	5.0	0.28	5-30	± 3	M2.8-M5.0	M2.2-M4.0
RGP-Q45LB	800	480	180	34	6.0	6.35	0.3	8-40	± 3	M3.3-M5.7	M2.7-M4.4
RGP-Q48LB	1700	790	215	42	6.0	8.0	0.55	5-45	± 3	M2.8-M5.8	M2.2-M4.7
RGP-Q50LB	1400	790	215	42	6.0	8.0	0.55	7-50	± 3	M2.9-M6.0	M2.6-M4.9
RGP-Q55LB	1000	790	215	42	6.0	8.0	0.55	7-65	± 3	M2.9-M6.4	M2.6-M5.4
RGP-Q60LB	550	790	215	42	6.0	8.0	0.55	15-95	± 3	M4.1-M7.0	M3.1-M6.0
RGP-Q65LB	300	810	215	42	6.0	8.0	0.55	30-180	± 3	M5.1-M9.3	M4.0-M7.2
RGP-Q68LB	250	810	215	42	6.0	8.0	0.55	50-250	± 3	M6.0-M11.0	M4.9-M8.7



Technical specification

Specification	Rotating speed (rpm)	Weight (G)	Length (mm)	Outer diameter (mm)	Air Pressure (Kg/cm ²)	Minimum Pipe Diameter (mm)	Air Consumption (m ³ min)	Torque Range (kgf.cm)	Precision (%)	Locking Ability	
										Mechanical tooth benchmark (T)	Self-tapping (2T)
RGP-Q10AB	1000	490	210	34	6.0	5.0	0.2	0.5-2	± 3	M1.0-M2.2	M1.1-M1.7
RGP-Q20AB	1000	660	270	34	6.0	5.0	0.2	1-8	± 3	M1.7-M3.3	M1.3-M2.7
RGP-Q30AB	1800	660	270	34	6.0	5.0	0.28	3-17	± 3	M2.2-M4.2	M1.7-M3.2
RGP-Q35AB	2200	660	270	34	6.0	5.0	0.28	3-20	± 3	M2.2-M4.5	M1.7-M3.5
RGP-Q38AB	1800	660	270	34	6.0	5.0	0.28	3-25	± 3	M2.2-M4.7	M1.7-M3.8
RGP-Q40AB	1000	660	270	34	6.0	5.0	0.28	5-30	± 3	M2.8-M5.0	M2.2-M4.0
RGP-Q45AB	800	660	270	34	6.0	6.35	0.3	8-40	± 3	M3.3-M5.7	M2.7-M4.4
RGP-Q48AB	1700	1200	235	42	6.0	8.0	0.55	5-45	± 3	M2.8-M5.8	M2.2-M4.7
RGP-Q50AB	1400	1200	235	42	6.0	8.0	0.55	7-50	± 3	M2.9-M6.0	M2.6-M4.9
RGP-Q55AB	1000	1200	235	42	6.0	8.0	0.55	7-65	± 3	M2.9-M6.4	M2.6-M5.4
RGP-Q60AB	550	1200	235	42	6.0	8.0	0.55	15-95	± 3	M4.1-M7.0	M3.1-M6.0
RGP-Q65AB	300	1200	235	42	6.0	8.0	0.55	30-180	± 3	M5.1-M9.3	M4.0-M7.2
RGP-Q68AB	250	1200	235	42	6.0	8.0	0.55	50-250	± 3	M6.0-M11.0	M4.9-M8.7

Gun Type



Technical specification

Specification	Rotating speed (rpm)	Weight (G)	Length (mm)	Outer diameter (mm)	Air Pressure (Kg/cm ²)	Minimum Pipe Diameter (mm)	Air Consumption (m ³ min)	Torque Range (kgf.cm)	Precision (%)	Locking Ability	
										Mechanical tooth benchmark (T)	Self-tapping (2T)
Start Mode: Push Start											
A8045P	1700	1200	235	42	6.0	8.0	0.55	5-45	± 3	M2.8-M5.8	M2.2-M4.7
A8050P	1400	1200	235	42	6.0	8.0	0.55	7-50	± 3	M2.9-M6.0	M2.6-M4.9
A8065P	1000	1200	235	42	6.0	8.0	0.55	7-65	± 3	M2.9-M6.4	M2.6-M5.4
A8090P	550	1200	235	42	6.0	8.0	0.55	15-95	± 3	M4.1-M7.0	M3.1-M6.0
A8160P	300	1200	235	42	6.0	8.0	0.55	30-180	± 3	M5.1-M9.3	M4.0-M7.2
A8250P	250	1200	235	42	6.0	8.0	0.55	50-250	± 3	M6.0-M11.0	M4.9-M8.7
Start Mode: Lever Start											
A8045L	1700	1200	235	42	6.0	8.0	0.55	5-45	± 3	M2.8-M5.8	M2.2-M4.7
A8050L	1400	1200	235	42	6.0	8.0	0.55	7-50	± 3	M2.9-M6.0	M2.6-M4.9
A8065L	1000	1200	235	42	6.0	8.0	0.55	7-65	± 3	M2.9-M6.4	M2.6-M5.4
A8090L	550	1200	235	42	6.0	8.0	0.55	15-95	± 3	M4.1-M7.0	M3.1-M6.0
A8160L	300	1200	235	42	6.0	8.0	0.55	30-180	± 3	M5.1-M9.3	M4.0-M7.2
A8250L	250	1200	235	42	6.0	8.0	0.55	50-250	± 3	M6.0-M11.0	M4.9-M8.7