


## Metric

Part#	Open Size	Shank Size	L mm	H mm	D mm	Weight g	Max. Torque N.m
OH94	4	9x12	175	4	22	35	2
OH95	5	9x12	175	4	22	35	4
OH95.5	5.5	9x12	175	5	22	38	5
OH96	6	9x12	175	5	22	38	6
OH97	7	9x12	175	5	22	38	9
OH98	8	9x12	175	5	22	37	13
OH99	9	9x12	175	5.5	26	44	18
OH910	10	9x12	175	5.5	26	43	24
OH911	11	9x12	175	5.5	26	42	32
OH912	12	9x12	175	7	30	48	41
OH913	13	9x12	175	7	30	47	51
OH914	14	9x12	175	8	35	58	63
OH915	15	9x12	175	8	35	57	77
OH916	16	9x12	175	8	38	56	92
OH917	17	9x12	175	8	38	54	109
OH918	18	9x12	25*	8	42	80	125
OH919	19	9x12	25*	8	42	75	145
OH920	20	9x12	25*	8	48	90	160
OH921	21	9x12	25*	8	50	100	160
OH922	22	9x12	25*	8	50	95	160
OH923	23	9x12	25*	8	53	100	160
OH924	24	9x12	25*	8	53	110	160
OH925	25	9x12	25*	8	53	110	160
OH926	26	9x12	25*	8	53	110	160
OH927	27	9x12	30*	8	64	140	160
OH928	28	9x12	30*	8	68	142	160
OH929	29	9x12	30*	8	68	142	160
OH930	30	9x12	35*	8	70	145	160
OH932	32	9x12	35*	8	70	145	160
OH933	33	9x12	35*	8	75	145	160
OH934	34	9x12	35*	8	80	145	160
OH935	35	9x12	35*	8	80	145	160
OH936	36	9x12	40*	8	80	145	160
OH937	37	9x12	45*	8	81	145	160
OH938	38	9x12	45*	8	82	145	160
OH939	39	9x12	45*	8	83	145	160
OH941	41	9x12	45*	8	85	145	160
OH942	42	9x12	50*	8	90	160	160
OH943	43	9x12	50*	8	100	165	160
OH944	44	9x12	50*	8	100	165	160
OH945	45	9x12	50*	8	100	165	160
OH946	46	9x12	50*	8	100	165	160
OH948	48	9x12	50*	8	104	175	160
OH949	49	9x12	50*	8	106	175	160
OH950	50	9x12	55*	8	106	175	160
OH951	51	9x12	55*	8	106	175	160
OH952	52	9x12	55*	8	110	175	160
OH953	53	9x12	55*	8	112	175	160
OH955	55	9x12	55*	8	116	175	160
OH960	60	9x12	60*	8	121	215	160
OH965	65	9x12	65*	8	126	225	160
OH967	67	9x12	65*	8	128	225	160
OH990	90	9x12	90*	8	165	300	160
OH146	6	14x18	25	7	32	120	6
OH147	7	14x18	25	7	32	120	9
OH148	8	14x18	25	7	32	120	13
OH149	9	14x18	25	7	32	118	18
OH1410	10	14x18	25	7	32	116	24
OH1411	11	14x18	25	7	32	114	32
OH1412	12	14x18	25	7	32	112	41
OH1413	13	14x18	25	7	32	110	51
OH1414	14	14x18	25	8	35	116	63
OH1415	15	14x18	25	8	35	115	77
OH1416	16	14x18	25	9	38	128	92
OH1417	17	14x18	25	9	38	127	109
OH1418	18	14x18	25	10	42	138	125
OH1419	19	14x18	25	10	42	137	145
OH1420	20	14x18	25	11	50	145	160
OH1421	21	14x18	25	11	50	158	190
OH1422	22	14x18	25	11	50	155	220
OH1423	23	14x18	25	13	53	156	250
OH1424	24	14x18	25	13	53	159	280
OH1425	25	14x18	25	13	53	163	320
OH1426	26	14x18	25	13	53	163	360
OH1427	27	14x18	30*	13	64	230	360
OH1428	28	14x18	30*	13	66	255	360
OH1429	29	14x18	30*	13	68	255	360
OH1430	30	14x18	35*	13	70	255	360
OH1431	31	14x18	35*	13	70	255	360
OH1432	32	14x18	35*	13	70	255	360
OH1433	33	14x18	40*	13	75	360	360
OH1434	34	14x18	40*	13	78	360	360
OH1435	35	14x18	40*	13	80	365	360
OH1436	36	14x18	40*	13	80	365	360
OH1437	37	14x18	45*	13	83	440	360
OH1438	38	14x18	45*	13	85	440	360
OH1439	39	14x18	45*	13	85	435	360
OH1440	40	14x18	50*	13	90	430	360
OH1441	41	14x18	50*	13	90	430	360
OH1442	42	14x18	50*	13	93	430	360
OH1443	43	14x18	50*	13	95	480	360
OH1444	44	14x18	50*	13	98	550	360
OH1445	45	14x18	50*	13	100	600	360
OH1446	46	14x18	50*	13	100	595	360
OH1447	47	14x18	50*	13	102	595	360



## Metric

Part#	Open Size	Shank Size	L mm	H mm	D mm	Weight g	Max. Torque N.m
OH1448	48	14x18	50*	13	104	595	360
OH1449	49	14x18	50*	13	106	610	360
OH1450	50	14x18	55*	13	106	610	360
OH1451	51	14x18	55*	13	106	600	360
OH1452	52	14x18	55*	13	110	600	360
OH1453	53	14x18	55*	13	112	600	360
OH1455	55	14x18	55*	13	116	585	360
OH1456	56	14x18	60*	13	120	650	360
OH1457	57	14x18	60*	13	121	650	360
OH1460	60	14x18	60*	13	121	650	360
OH1461	61	14x18	60*	13	121	640	360
OH1462	62	14x18	60*	13	122	640	360
OH1465	65	14x18	65*	13	126	680	360
OH1466	66	14x18	65*	13	128	680	360
OH1468	68	14x18	70*	13	130	690	360
OH1470	70	14x18	70*	13	135	700	360
OH1472	72	14x18	70*	13	135	690	360
OH1475	75	14x18	75*	13	142	720	360
OH1478	78	14x18	75*	13	150	730	360
OH1480	80	14x18	80*	13	155	750	360
OH1485	85	14x18	80*	13	155	750	360
OH1488	88	14x18	90*	13	160	775	360
OH1490	90	14x18	90*	13	165	800	360
OH2417	17	24x32	35	25	62	650	1200
OH2419	19	24x32	35	25	65	680	1200
OH2420	20	24x32	35	25	66	680	1200
OH2422	22	24x32	35	25	68	700	1200
OH2424	24	24x32	35	25	70	715	1200
OH2425	25	24x32	35	25	70	715	1200
OH2426	26	24x32	35	25	70	715	1200
OH2427	27	24x32	35	25	72	718	1200
OH2428	28	24x32	35	25	72	719	1200
OH2430	30	24x32	35	25	75	720	1200
OH2432	32	24x32	35	25	76	725	1200
OH2434	34	24x32	40*	25	78	730	1200
OH2436	36	24x32	40*	25	80	735	1200
OH2438	38	24x32	45*	25	91	809	1200
OH2441	41	24x32	50*	25	95	925	1200
OH2445	45	24x32	50*	25	100	1000	1200
OH2446	46	24x32	50*	25	100	1000	1200
OH2448	48	24x32	50*	25	104	1100	1200
OH2450	50	24x32	55*	25	106	1150	1200
OH2455	55	24x32	55*	25	119	1300	1200
OH2457	57	24x32	55*	25	120	1330	1200
OH2460	60	24x32	60*	25	121	1330	1200
OH2465	65	24x32	65*	25	130	1337	1200
OH2467	67	24x32	70*	25	130	1415	1200
OH2470	70	24x32	70*	25	132	1620	1200
OH2475	75	24x32	75*	25	150	1650	1200
OH2727	27	27x36	50	28	90	1250	3000
OH2730	30	27x36	50	28	95	1295	3000
OH2732	32	27x36	50	28	95	1295	3000
OH2734	34	27x36	50	28	100	1330	3000
OH2736	36	27x36	50	28	100	1335	3000
OH2738	38	27x36	50	28	107	1338	3000
OH2741	41	27x36	50	28	107	1440	3000
OH2742	42	27x36	50	28	107	1440	3000
OH2745	45	27x36	50	28	107	1440	3000
OH2746	46	27x36	50	28	114	1445	3000
OH2750	50	27x36	55*	28	118	1450	3000
OH2755	55	27x36	55*	28	124	1455	3000
OH2760	60	27x36	60*	28	130	1460	3000
OH2761	61	27x36	65*	28	131	1462	3000
OH2765	65	27x36	65*	28	136	1462	3000
OH2770	70	27x36	70*	28	142	1465	3000
OH2775	75	27x36	75*	28	148	1780	3000
OH2780	80	27x36	80*	28	158	2600	3000
OH2785	85	27x36	85*	28	164	2850	3000
OH2790	90	27x36	90*	28	176	2900	3000
OH2795	95	27x36	95*	28	180	3000	3000

\* Length size with \*\* mark are special fittings, you should adjust the torque according to torque wrench manual, see page 15